



For compaction of sand, gravel and rock fill.

All our machine models are versatile and easy to operate. They are also durable and reliable, which means lower operating and maintenance costs.

- The SWEpac F 50 is suitable for smaller jobs, such as adjusting the subsurface for paving bricks and stones.
- With a Vulkollan® plate (accessory) attached to the base, it can compact paved areas efficiently for an even surface.
- The machine can cope with the toughest of jobs since parts of the motor and transmission are fully enclosed in a rugged polythene casing.
- The handle can be easily removed without any tools, and the machine can be transported in the trunk of a regular-sized car.
- The chassis is hot-dip galvanized, which means superior maintenance-free corrosion protection.

TECHNICAL DATA

SWEpac F 50

Net, weight	52 kg
Base plate, width	300 mm
Height, max / min	1010 / 700 mm
Length, max / min	1125 / 565 mm
W x H x L (without handle)	300 x 385 x 500 mm
Engine	Honda GX 100
Fuel tank capacity	2.5 liter
Fuel	Unleaded or alkylate petrol
Engine output, max	2.4 kW
Centrifugal force	9 kN
Working speed	0 - 25 m/min
Hand/arm vibrations a_{hv} according to ISO 5349 on gravel surface	4.5 m/s ²
Guaranteed sound-power level, L_{WA}	105 dB(A)
Sound pressure level (at operators ear)	89 dB(A)

Part number

305050	F 50 with Honda petrol engine
--------	-------------------------------

Accessories

305039	Vulkollan plate complete
--------	--------------------------

F50_2013-03_GB