

SWEPAC



F 75

Forward
vibratory plate

For compaction of sand, gravel, rock fill and paving stones.

All our machine models are versatile and easy to operate. They are also durable and reliable, which means lower operating and maintenance costs.

- The SWEpac F 75 is suitable for smaller jobs, such as adjusting the subsurface for pavers.
- With a Vulkollan® plate (accessory) attached to the base, it can compact paved areas efficiently for an even surface.
- The machine can cope with the toughest of jobs since parts of the motor and transmission are fully enclosed in a rugged polythene casing. The chassis and handle are hot-dip galvanized and maintenance-free.
- The excentric element has permanently lubricated bearings that require no maintenance.
- The handlebar can easily be removed without any tools, for instance, for transportation.

TECHNICAL DATA

SWEpac F 75

Net, weight	75 kg
Base plate, width	380 mm
Height, max / min	1000 / 920 mm
Length, max / min	920 / 600 mm
Engine	Honda GX 120
Fuel tank capacity	2.5 liter
Fuel	Unleaded or alkylate petrol
Engine output, max	2.9 kW
Centrifugal force	11 kN
Working speed	0 - 25 m/min
Hand/arm vibrations a_{hv} according to ISO 5349 on gravel surface	4.6 m/s ²
Guaranteed sound-power level, L_{WA}	105 dB(A)
Sound pressure level (at operators ear)	90 dB(A)

Part number

305100	F 75 with Honda petrol engine
--------	-------------------------------

Accessories

305138	Vulkollan plate complete
--------	--------------------------

F75_2013-03_GB

MEERMANMACHINES

MEERMAN GROEP

Meerman Machines bv ■ Hoekerstraat 10 ■ 3133 KR Vlaardingen

T: +31(0)10-4350611 ■ F: +31(0)10-4355026 ■ info@meerman.nl ■ www.meerman.nl